

GETIG 308L

IDENTIFICATION: ER 308L

SPECIFICATIONS: AWS /SFA 5.9: ER 308L; DIN 8556-86 WSGX2 CrNi199; BS 2901-90 308S92

CHARACTERISTICS: Extra low carbon Austenitic Stainless Steel Filler Rod.

CHARACTERISTICS:

An extra low carbon 20/10 filler rod which has excellent resistance to intergranular corrosion due to its extra low carbon content. The weld deposit is corrosion and scale resistant and free from porosity. The deposited weld metal meets X-ray/ radiographic quality. Good resistance to oxidizing acids and reducing adds.

COMPOSITION OF THE WIRE (RANGE) %

C	Mn	Si	S	P
0.025 max	1.0- 2.5	0.30- 0.65	0.020 max	0.030 max
Cr	Cu	Mo	Ni	
19.5- 22	0.50 max	0.5 max	9.0- 11.0	

APPLICATIONS:

- For welding of 19/10 austenitic stainless steel plates of the type AISI 301, 302, 304, 304L, sheets, pipes and tubes used in chemical plants, fertilizer plants, oil refineries, food and dairy industries.
- Can be used for welding stabilized stainless steel 347 & 321 provided service temperatures for structural application are below 400°C.
- Also used for making furniture, hospital and kitchen equipments etc.

ALL WELDMECHANICAL PROPERTIES

UTS (MPa)	YS (MPa)	ELN (%) (L=4D)	CVN impact strength	
			Temp	Joules
520 min	430 min	35 min	20°C	80-140
			-196°C	30-60

SHIELDING GAS: GAS Argon, 99.99%, 6-12 l/min

Packing Specifications: Supplied in cut lengths of 1 meter packed in 5 kgs cartons)

RECOMMENDED CURRENT AND PACKING DATA:

SIZE (MM)	RECOMMENDED CURRENT (AMPS) DC (-)	LENGTH (MM)	KG/PKT (KG)
1.6	100-200	1000	5.00
2.0	150-250	1000	5.00
2.5	200-300	1000	5.00
3.20	300-400	1000	5.00

Manufactured by: GEE LIMITED

Regd. Off & Works: plot No.B - 12, MIDC, Kalyan-Bhiwandi Road, Saravli, Kalyan (West)
Thane, Maharastra, India.
Website: www.geelimited.com

Authorised Distributor: CROSS MARKETING

Head Office: Martin Burn Business Park | Suite No 900A | Block- BP | Salt Lake | Sector - V | Kolkata - 700091 | West Bengal | India
Ph: (+91) 9163763419 | (+91) 9038320189
Email: lakhotia.ravi@gmail.com | crossmarketingkolkata@gmail.com